



EYEWASH W/STAINLESS STEEL BOWL AND WALL MOUNT

PART NUMBER:01045001

SPECIFICATION:

Third party certified to ANSI Z358.1, the eyewash shall deliver 2.4 gpm (9.1 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with ½” chrome plated (CP) single motion activation stay open ball valve with CP ball. Eyewash shall include stainless steel (SS) actuator with actuation graphic, 7” X 11” (17.8cm X 27.9cm) sign and SS wall mounting bracket. Unit must be supplied with self-adjusting 2.4 gpm (9.1 lpm) regulator to assure a constant and even dual stream flow pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Eyewash heads with integral hinged covers to be manufactured of solvent resistant acetal mounted on chrome plated brass wye in a type 304 SS bowl. Eyewash covers are provided to inhibit dust and/or contamination when not in use. Eyewash units with deteriorating screens/filters are not acceptable.

Encon Safety Products Model 01045001 includes eyewash with stainless steel bowl and wall mount.

Encon Safety Products Model 01045010 includes eyewash with stainless steel bowl, wall mount and 1 ¼” p-trap.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

PIPING: ½” Chrome plated brass.

VALVES: ½” Chrome plated bronze stay open ball valve with chrome plated ball, stainless steel valve stem and stainless steel push plate with actuation graphic.

HEAD: Acetal dual stream heads with integral hinged covers and chrome plated brass wye assembly.

BOWL: Type 304 stainless steel bowl with S/S wall mount bracket

REGULATOR: Self-adjusting (2) 1.2 gpm (4.5 lpm) regulators.

SUPPLY: ½” NPT

WASTE: 1 ¼” NPT (1 ¼” tailpiece and p-trap optional).

WEIGHT: 9 lbs (4.08 kgs)

